This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An apparatus for inoculating a biological substrate with cells comprising:

a container for receiving said substrate and a suspension of said cells;

first drive <u>adapted</u> means for rotatably supporting said container <u>for rotation through</u> 360° about a first rotational axis extending through said container; and

second drive <u>adapted</u> means for rotatably supporting said first drive <u>for rotation</u> through 360° means about a second rotational axis whereby said container revolves <u>continuously</u> around said second rotational axis while said container <u>is</u> rotating about said first axis;

wherein said first and second rotational axes lie in mutually <u>spaced</u> spaces apart planes and extend in different directions in said planes.

- 2. (Previously Presented) The apparatus according to claim 1, wherein said first and second axes extend neither in parallel nor intersecting with each other.
- 3. (Currently Amended) The apparatus according to claim 1 wherein said first and second rotational axes extend in angularly spaced apart directions defining approximately 90° about a center line that intersects perpendicularly perpendicularly both said first and second rotational axes.
- 4. (Previously Presented) The apparatus according to claim 1 wherein at least one of said first and second rotational axes is offset from the drive shaft of a mechanism for rotating said container or said first drive means.
- 5. (Previously Presented) The apparatus according to claim 1 wherein said container is removably mounted in said first drive means.
 - 6. (Previously Presented) The apparatus according to claim 1 wherein said first

drive means is removably mounted in said second drive means.

- 7. (Previously Presented) The apparatus according to claim 1 wherein said first and second drive means include their own control means for controlling the rotation of said container and said first drive means independently from the other control means.
- 8. (Previously Presented) The apparatus according to claim 1 wherein said first drive means transmit a driving force to said container via frictional contact between them.
- 9. (Previously Presented) The apparatus according to claim 1 wherein said second drive means transmit a driving force to said first drive means via frictional contact between them.
- 10. (Withdrawn and Currently Amended) A method for inoculating a biological substrate with cells by an apparatus according to claim 1, comprising the steps of:

receiving said substrate and a suspension of said cells in a container;

rotatably supporting said container in the first drive means for rotation through 360° about the a first rotational axis extending through said container;

rotating said container about said first rotational axis and said first drive through 360° means about said second rotational axis whereby said container revolves continuously about said second rotational axis while said container is rotating about said first rotational axis;

wherein said first and second rotational axes lie in mutually spaced apart planes and extend in different directions in said planes.

11. (Withdrawn and Currently Amended) A method for inoculating a biological substrate with cells by an apparatus according to claim 1, comprising the steps of:

receiving said substrate and a suspension of said cells in a container;

rotatably supporting said container in <u>the</u> first drive means for rotation <u>through 360°</u> about <u>the</u> a first rotational axis <u>extending through said container</u>;

rotatably supporting said first drive means in the second drive means for rotation about the a second rotational axis;

rotating said container about said first rotational axis and said first drive through 360°

means about said second rotational axis whereby said container revolves <u>continuously</u> around said second rotational axis while said container is rotating about said first rotational axis;

wherein said first and second rotational axes extend neither in parallel nor intersecting with each other.

- 12. (Withdrawn and Currently Amended) The method according to claim 10 wherein said first and second rotational axes extend in angularly spaced apart directions defining approximately 90° about a center line that intersects perpendicularly perpendicularly both said first and second rotational axes.
- 13. (Withdrawn and Currently Amended) The method according to claim 10 wherein at least one of said first and second rotational axes is offset from the drive shaft of a drive mechanism for rotating said container or said first drive means.
- 14. (Withdrawn and Currently Amended) The method according to claim 10 wherein said container is removably mounted in said first drive means.
- 15. (Withdrawn and Currently Amended) The method according to claim 10 wherein said first drive means is removably mounted in said second drive means.
- 16. (Withdrawn and Currently Amended) The method according to claim 10 wherein said first and second drive means include their own control means for controlling the rotation of said container and said first drive means independently from the other control means.
- 17. (Withdrawn and Currently Amended) The method according to claim 10 wherein said first drive means transmit a driving force to said container via frictional contact between them.
- 18. (Withdrawn and Currently Amended) The method according to claim 10 wherein said second drive means transmit a driving forth to said first drive means via frictional contact between them.